

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-309676
(43)Date of publication of application : 07.11.2000

(51)Int.Cl. C08L 53/02
C08K 5/01
C08L 23/08
C08L 23/10
C08L 23/16
C08L 23/18

(21)Application number : 11-119973 (71)Applicant : MITSUBISHI CHEMICALS CORP
(22)Date of filing : 27.04.1999 (72)Inventor : SHIN GAKUJI
KAMEI HIDEKI

(54) THERMOPLASTIC ELASTOMER COMPOSITION

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a thermoplastic elastomer composition excellent in flexibility, mechanical strength, thermofusing strength and profile extrusion molding processability, slight in stickiness of the products, and also slight in bleeding.

SOLUTION: This composition comprises the following four components 1 to 4: (1) 30-70 wt.% of a hydrogenated product with a weight-average molecular weight of 100,000-450,000 made from a block copolymer A made up of polymer block composed of vinyl aromatic hydrocarbon unit and polymer block B composed of conjugated diene unit, wherein the polymer block A accounts for 10-50 wt.% of the copolymer, (2) 70-30 wt.% of a hydrocarbon-based rubber flexibilizer, (3) 3-50 wt.% of a propylene-based polymer with a melt flow rate (MFR) of 0.01-100 g/10 min, and (4) 3-80 wt.% of a copolymer with a melt flow rate (MFR) of 1-40 g/10 min and density of 0.86-0.91 g/cm³ made from ethylene and a 4-20C α -olefin.

LEGAL STATUS

[Date of request for examination] 16.05.2003
[Date of sending the examiner's decision of rejection]
[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]
[Date of final disposal for application]
[Patent number] 3702704
[Date of registration] 29.07.2005
[Number of appeal against examiner's decision of rejection]
[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]